

LATEX POWDER FREE

PROTECTIVE GLOVES

Single use | Ambidextrous | Fingertip textured | Non-Sterile



CONFIDENTIAL
Cannot be copied or amended for purposes other than
authorised by MIS Healthcare for its intended use.

Functional Benefits

- Beaded cuff makes donning easy and helps prevent roll back
- Superior strength with better puncture resistance
- Finger texture enhances wet and dry grip
- Thinner film barrier improves tactile sensitivity
- Custom design enhances comfort and fit



Quality Standards

Conforms to ASTM D3578 standards

Glove Sizes

Small, Medium, Large, Extra-large

Product Specifications

Product description	: Non-sterile, powder-free NR Latex protective gloves
Material	: Natural Rubber Latex (NRL)
Design	: Ambidextrous, standard beaded cuff and fingertip textured
Feature	: Powder free, online chlorinated
Color	: Natural White
Product conformance	: ASTM D3578
Product packaging mode	: 100 gloves per box by weight : 10 boxes per carton
Storage	: The glove shall maintain their properties when stored in a dry condition. Avoid direct sunlight
Shelf-life	: 3 years from the date of manufacturing

CAUTION: This product contain natural rubber latex which may cause allergic reactions, including anaphylactic responses.





Product specification					
Glove length (mm)		Glove palm width (mm)			
ASTM D3578	*MS Glove Product performance	S	M	L	XL
S -220, min, M, L, XL -230, min	All sizes S, M, L, XL ≥ 240	80 ±10	95 ±10	110 ±10	120 ±10

*Internal control value shall not be taken as product specification.

Glove's thickness (mm) (measured in single wall)	Specification	
	ASTM D3578	*MS Glove product performance
Finger (13 ±3mm from fingertip)	0.05, min	0.08, min
Palm (Approximate center of palm, with respect to glove size)	0.05, min	0.08, min
Cuff (Approximate 25±5mm from the cuff edge)	NA	0.06, min

*Internal control value shall not be taken as product specification

Physical properties	Before aging	After accelerated aging (7 days at 70 ±2°C)
Tensile strength (MPa)	18, min	14, min
Stress at 500% Elongation (MPa)	5.5, max	NA
Ultimate Elongation (%)	650, min	500, min

Product performance requirements	Inspection level	AQL
1000mL Watertightness	G1	2.5
Physical dimensions	S2	4.0
Physical properties	S2	4.0
Visual defects – Critical	G1	4.0

(ISO2859-1, Sampling Procedures For Inspection By Attributes)